

APPLICATION CHART

Motorcycle

FRONT Tire Width	Ounces Required
80mm-120mm	1
130mm-240mm	2
240mm - Up	3

REAR Tire Width	Ounces Required
130mm-240mm	2
250mm-360mm	3
195-205 Car Tire on Rear	3

Scooters	Ounces Required
10" Rim Diameter	1
12" & Up Rim Diameter	2

Dual Purpose, Dirt Bike w/Rim Lock	Ounces Required
Front 80mm-120mm	2
Rear 130mm-230mm	3

Tube Type Tire, Wire Spoke Rim	Ounces Required
80mm-120mm	2
130mm-240mm	2

Harley-Dunlop Tire Size Conversion (MT90B16)

MT, MH, MJ etc = Tire Width, 90 = Tire Profile, B = Rim Diameter

MH = 80mm Width	MR = 120mm Width
MJ = 90mm Width	MT = 130mm Width
MM = 100mm Width	MU = 140mm Width
MN or MP = 110mm Width	MV = 150mm Width

PLEASE NOTE EXCEPTIONS BELOW

- 1) Super Sport bikes can experience a vibration at high triple digit speeds because too much product was added. Please start with 1/2oz in the front tire, regular recommended amount in the rear.

(ZX1000, CBR1000RR, CBR600RR, ZX600R, R1, R6, RC8, etc)



EXAMPLE:

WIDTH / ASPECT RATIO x RIM DIAMETER

110/90x19